

STONERENU



STONERENU is a waterbased, low VOC, clear coating designed for high performance sealing and appearance enhancement. It is designed specifically to seal and restore the luster of aesthetic stone surfaces such as marble, granite, slate, tile, etc. that contain natural silica. It can be used on interior and exterior, horizontal and vertical surfaces due to its outstanding adhesion and wearability. It has excellent, water, solvent, grease, oil and stain resistance and prevents scratching and marring. **STONERENU** helps rejuvenate the sheen and beauty of stone surfaces that have become dull through use, without the need for expensive and messy polishing services. Some of the areas that can benefit through application of **STONERENU** include bathrooms, hallways, kitchen floors, countertops, vanities, etc. **STONERENU**, can also be used to seal and protect concrete, slate, tile, brick and similar materials. **STONERENU** is available in high gloss, satin and flat finishes and it can be stained or pigmented, if necessary, without comprising the protective features.



COVERAGE: Coverage ranges from 250 to 400 square feet per gallon depending on surface texture and porosity. **STONERENU** goes on easily and dries to a crystal clear finish. Always test each surface for appearance and penetration before proceeding with application on the entire surface.

APPLICATION: **STONERENU** may be applied by brush, roller or low pressure airless spray. At 77°F and 50% RH the coating should be dry to the touch in less than 30 minutes. The time may vary based on prevailing conditions. One coat is usually sufficient however if a second coat is desired for greater gloss and/or protection, allow a minimum of 30 to 60 minutes between coats. The coated surface can be subjected to light foot traffic after it is fully dry. Allow 24 hours time for optimal curing before subjecting the coating to heavy traffic. Prior to application make sure that washed surface is allowed to thoroughly dry. Do not apply at temperatures below 50°F or above 90°F. Hold off the application if rain or heavy dew is imminent. Avoid heavy buildup, puddling, and excessive overlapping of sealer. Refer to the Preparation & Application instructions, on the label, for greater detail.

CLEANUP: Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.