



**TEAKPROTEK** is a unique water based formulation aimed at addressing a needed solution for marine teak decks. This crystal clear, odor and fume free coating has outstanding adhesion and abrasion resistance. Teak decks coated with TeakProtek will retain their protection for a year or longer. In addition to water, soil and stain protection, the teak wood is protected against harmful UV rays, preventing oxidizing and break down of the wood fiber.

Popular teak coatings are topical with short term protection. Some contain modest UV protection and thus call for repeat applications. Others are dilutions of linseed or tung oil in mineral spirits and with repeat applications they can build up a sticky layer that can trap moisture and damage the wood. **TEAKPROTEK** has been formulated with highly specialized, multiple UV inhibitors as this is the single most detrimental influence that has to be controlled. Additionally **TEAKPROTEK** provides a durable barrier against water, beverages and other soils and staining. It also contains certain nano materials that increase the coefficient of friction and provide anti-slip properties even under wet conditions.

**TEAKPROTEK** can be used on solid woods, veneers and all natural woods such as maple, oak, pine, walnut, rosewood, etc. The application of **TEAKPROTEK** will brighten the natural color of the wood without obscuring the wood grain and natural appearance. **TEAKPROTEK** is available in a satin or matte finish surface and the fully cured coating exhibits a strong water beading effect. When necessary a re-finish coat can be applied after a light sanding. There is no need to fully remove the previous **TEAKPROTEK** coat or other extensive prep work. Simply make sure that the surface to be treated is clean and free of dirt and soil.

**COVERAGE:** Coverage of **TEAKPROTEK** is dictated by the wood's density and surface preparation. Soft woods tend to absorb more coating. These factors impact the coverage which can range from 250 square feet to 400 square feet per gallon, and possibly greater.

**APPLICATION:** **TEAKPROTEK** may be applied by brush or roller on wood that is fully dry. Normal surface preparation methods such as acid washing, sanding, etc. are sufficient. Generally a single coat is recommended with most teak deck applications. If a second coat is desired allow the first coat 45 minutes to an hour to get absorbed in the wood and then proceed with the second coat. Depending on the ambient temperature the treated deck should be available for walking and general light use after a couple of hours. Over the next 24 to 48 hours the coating will internally cross link and achieve optimal physical properties.

**TEAKPROTEK** goes on very easily and dries to a clear finish. It will brighten the appearance of the wood and enhance the wood grain and general patina. Fully cured **TEAKPROTEK** will show pronounced water beading and provide protection from staining, fungal growth and UV degradation. **TEAKPROTEK** has good storage stability when kept in air tight containers. It should be stored away from heat and high temperatures.

**APPLICATION & CLEANUP:** Clean spills, spatters and tools with clean water. Similarly if application was completed via spraying, flush spray equipment with water to prevent clogging and malfunction.